



**MB75**

**Electrical specification:**

Voltage:	<b>12V</b>	(V)
Capacity:	<b>75</b>	(Ah)
Cold cranking current:	<b>540</b>	(A, EN)
Cold cranking current:	<b>335</b>	(A, DIN)

**Mechanical specification:**

Dimensional group:	-	EN50342-2:2009
ETN reference:	<b>G56J8K0_1</b>	
DIN reference:	-	
Sizes:	<b>270x175x220</b>	(L x W x H)
Cell Layout:	<b>1</b>	
Terminal Type:	<b>1</b>	

**Container**

<b>Case:</b>	Material	<b>POLYPROPYLENE</b>	Colour	<b>Black</b>
	Bottom hold down	<b>B19</b>	Handles	-
<b>Lid:</b>	Material	<b>POLYPROPYLENE</b>	Colour	<b>Black</b>
	Cover design	<b>KAMINA</b>	Handles	<b>Black</b>
<b>Vent cap:</b>	Material	<b>POLYPROPYLENE</b>	Colour	<b>Black</b>
	Type	<b>KAMINA</b>		

**Test details:**

Vibration resistance:	<b>V1</b>	Battery weight	<b>11.30</b>	±0.80	(kg)
Endurance resistance:	<b>E1</b>	Acid weight	<b>5.9</b>	±0.40	(kg)
		Total battery weight	<b>17.20</b>	±1.20	(kg)

**Separator:** Type

**According to:**

<b>PE</b>
<b>EN 50342</b>

